




Cutting Applications





- The paddles are positioned to move materials in opposing lateral directions and radially.
- The paddle design is normally applied where friable materials are being blended
- Items Like Pickles, Vegetables with Rice or with Meat can be mixed.

High Capacity Double T-Bar Mixers

Model No.: HEDB 100 ~ HEDB 500D

Giantwell Machinery Company Ltd.-Taiwan

Many Options like Self Lifting Lid, Speed Control, Different Types of Discharges can be given with the Machine.

- Technical Specifications:
- Double shaft Mixer
- 1400 (L) x 730 (W) x 1250 (H)
- Drum Size : 610 (L) x 645 (W) x 625 (H)
- 3 HP Motor With reducer
- Total time setting
- Fwd/Rev. time setting.
- Tilting Discharge by Hand
- Power : 3HP/3ph/50HZ
- Capacity : 90~100(Liter) HEDB-500D
- Double shaft Mixer
- 2530 (L) x 830 (W) x 1300 (H)
- Drum Size : 1500 (L) x 750 (W) x 655 (H)
- 7.5 HP Motor With reducer
- Total time setting
- Fwd/Rev. time setting.
- Tilting Discharge by Power
- Power : 7.5HP/3ph/50HZ
- Capacity : 480~500(Litre)
 HEDB-500AD HEDB-500D+INVERTER
- Power : 7.5HP/3ph/50HZ

Note : Technical specifications are subject to change without prior notice due to ongoing research & developments.

FEATURES

• Double T Bar Mixers consist of a U-shaped horizontal trough and a specially fabricated T Shaped Paddles mounted on Two Shafts .

Office : KH No : 411, G/F, Street No. 6, Block A, Mahipalpur, New Delhi : 110037 (INDIA) Tele Fax : + 91 11-26788776 Contact : +91 98101 38678 Email: info@ecocosmos.com